GLORY ADVANCED

ESPECIFICACIONES

CUADRO	
TALLAS	S/M, M/L, L/XL
COLORES	Shoreline/Carbon
CUADRO	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
HORQUILLA	Fox 40 Factory, GRIP2 damper, 203mm, 20x110, custom tuned for Giant
AMORTIGUADOR	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M #425, M/L #450, L/XL #475
COMPONENTES	
MANILLAR	Giant Contact SL TR35, composite, 800x35mm, 20mm rise
PUÑOS	Giant Tactal Pro Single
POTENCIA	TruVativ Descendant Direct Mount, 35 S/M:50mm, M/L:50mm, L/XL:50mm
TIJA DE SILLÍN	Giant Contact, 30.9mm, 0 offset, 400mm
SILLÍN	Giant Romero
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM GX Eagle DH, 1x7
DESVIADOR	N/A
CAMBIO TRASERO	SRAM GX Eagle DH
FRENOS	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors, [F]220mm, [R]203mm
PALANCAS DE FRENOS	Shimano Saint BL-M820
CASETTE	SRAM GX DH, 11-25
CADENA	SRAM PC 1110
JGO. PLATOS Y BIELAS	TruVativ Descendent DH, 34t, 56.5mm chainline, S/M:165mm, M/L:170mm, L/XL:170mm
CAJA DE PEDALIER	SRAM DUB, threaded, 83mm

RUEDAS	
LLANTAS	Giant AM30, alloy, 28-hole, 30mm inner width
BUJES	[F] alloy, sealed cartridge, 6-bolt, 20x110mm [R] alloy, 72t pawl driver, sealed cartridge, 6-bolt, 12x157mm
RADIOS	Sapim Laser, straight pull, DBL
CUBIERTAS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full downtube protector. *Not compatible with 2023 or earlier RockShox BoXXer Ultimate or BoXXer Select

GEOMETRÍA

CUADRO	S/M	M/L	L/XL
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH
Longitud del tubo del sillín (mm)	430	450	450
Seat Post Insertion Depth (mm)	155	165	165
Ángulo del tubo del sillín	78,4° | 78,7° | 79,1°	78,4° | 78,8° | 79,1°	78,5° | 78,8° | 79,1°
Longitud del tubo superior (mm) (mm)	571,2 | 570,5 | 569,8	591,3 | 590,5 | 589,8	611,3 | 610,6 | 609,8
Longitud del tubo de dirección (mm)(mm)	110	110	110
Ángulo del tubo de dirección	61,6° | 61,9° | 62,3°	61,6° | 62,0° | 62,3°	61,7° | 62,0° | 62,3°
Inclinación de la horquilla (mm)	52	52	52
Trail (mm) (mm)	146,4 | 143,6 | 140,8	146,2 | 143,5 | 140,8	146 | 143,3 | 140,8
Distancia entre ejes (mm) (mm)	1273 | 1271,9 | 1270,6	1293 | 1291,8 | 1290,6	1313 | 1311,9 | 1310
Longitud de la vaina (mm)(mm)	447,9 | 446,5 | 445	447,9 | 446,5 | 445	447,9 | 446,5 | 445
Caída del eje de pedalier (mm) (mm)	13,1 | 8,1 | 3	13,3 | 8,3 | 3,1	13,5 | 8,4 | 3,2
Stack (mm) (mm)	634,6 | 631,9 | 629,1	634,9 | 632,2 | 629,2	635,3 | 632,4 | 629,3
Reach (mm) (mm)	440,9 | 444,7 | 448,6	461,2 | 464,9 | 468,6	481,5 | 485,1 | 488,6
Altura del suelo al tubo (mm) (mm)	733,7 | 738,2 | 742,9	735,2 | 740 | 744,8	742,9 | 747,6 | 752,3
Ancho del manillar (mm) (mm)	800	800	800
Longitud de la potencia (mm) (mm)	50	50	50
Longitud de las bielas (mm) (mm)	165	165	165
Tamaño de ruedas	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"	[R] 27.5" / [F] 29"

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.