



## ESPECIFICACIONES

CUADRO	
TALLAS	27.5": XS, S, 29": S, M, L
COLORES	Tyrian Purple, Golden Wheat
CUADRO	ALUXX-grade aluminum, disc
HORQUILLA	SR Suntour XCE, QR, steel steerer 27.5" XS: 80mm, S: 80mm 29" S: 100mm, M: 100mm, L: 100mm
AMORTIGUADOR	N/A
COMPONENTES	
MANILLAR	Giant Connect Trail, 31.8mm 27.5" XS: 690mm, S: 690mm 29" S: 750mm, M: 750mm, L: 750mm
PUÑOS	Giant Sole-O
POTENCIA	Giant Sport, 7-degree 27.5" XS: 40mm, S: 40mm 29" S: 40mm, M: 50mm, L: 50
TIJA DE SILLÍN	Giant Sport, 30.9mm 27.5" XS: 100x350mm, S: 100x350mm 29" S: 100x350mm, M: 100x375mm, L: 100x375mm
SILLÍN	Contact Ergo
PEDALES	MTB caged
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano, Altus 2x8, SL-M315-2L, SL-M315-8R
DESVIADOR	Shimano, Altus, FD-M315-TS
CAMBIO TRASERO	Shimano, Acera 2x8, RD M3020-8
FRENOS	Tektro HDC TKD 149, hydraulic, Tektro rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Tektro TKD 149, for small hands
CASSETTE	Shimano, Altus, CS-HG31-8, 11-34
CADENA	KMC 8.3
JGO. PLATOS Y BIELAS	Shimano Acera FC-M315-2, 22/36, 49mm chainline 27.5" XS: 170mm, S: 170mm 29" S: 170mm, M: 170mm, L: 170mm
CAJA DE PEDALIER	cartridge

RUEDAS	
LLANTAS	27.5": Giant GX03V 27.5", alloy, double wall, 21mm inner width 29": Giant GX03V 29", alloy, double wall, 21mm inner width
BUJES	alloy, sealed bearing
RADIOS	stainless, 14g
CUBIERTAS	Maxxis Ikon 27.5x2.2" or 29x2.2", 60tpi wire bead
EXTRAS	2.4" max tire size, max chainring 32T

## GEOMETRÍA

CUADRO	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")
Longitud del tubo del sillín (mm)	330	365	380	410	450
Seat Post Insertion Depth (mm)	280	310	330	360	220
Ángulo del tubo del sillín	74,0°	74,0°	74,5°	74,5°	74,0°
Longitud del tubo superior (mm) (mm)	538	558	571	599	610
Longitud del tubo de dirección (mm) (mm)	90	95	90	100	105
Ángulo del tubo de dirección	67,0°	67,0°	67,5°	67,5°	68,5°
Inclinación de la horquilla (mm)	44	44	44	44	51
Trail (mm) (mm)	105,2	105,2	108,9	108,9	94,3
Distancia entre ejes (mm) (mm)	1080	1101	1129	1158	1160
Longitud de la vaina (mm) (mm)	440	440	455	455	455
Caída del eje de pedalier (mm) (mm)	45	45	55	55	55
Stack (mm) (mm)	548	553	593	602	610
Reach (mm) (mm)	381	400	407	432	435
Altura del suelo al tubo (mm) (mm)	680	689	689	708	757
Ancho del manillar (mm) (mm)	690	690	750	750	750
Longitud de la potencia (mm) (mm)	40	40	40	50	50
Longitud de las bielas (mm) (mm)	165	165	170	170	175
Tamaño de ruedas	27.5"	27.5"	29"	29"	29"

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.