TALON 0

SPECS

FRAME	
SIZES	27.5: XS, S, 29: S, M, L, XL, XXL
COLOURS	Stealth Chrome, Plasma Coral
FRAME	ALUXX-grade aluminum, disc
FORK	SXC32-2 RCL, air spring, thru axle, steel steerer, 15x110 XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29) M:100mm travel (29) L: 100mm travel (29) XL: 100mm travel (29) XXL: 100mm travel (29)
COMPONENTS	
HANDLEBAR	Giant Connect Trail, 31.8mm XS: 690mm (27.5) S: 690mm (27.5) / 750mm (29) M: 780mm (29) L: 780mm (29) XL: 780mm (29) XXL: 780mm (29)
GRIPS	Giant Sole-O
STEM	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (29) L: 70mm (29) XL: 80mm (29) XXL: 90mm (29)
SEATPOST	Contact Switch AT Core, 30.9, dropper, remote under bar, 110-140mm travel XS: 395mm (27.5) S: 395mm (27.5/29) M: 395mm (29) L: 395mm (29) XL: 395mm (29) XXL: 395mm (29)
SADDLE	Giant ErgoContact Trail
PEDALS	MTB caged
DRIVETRAIN	
SHIFTERS	Shimano Deore M6200, 1x12
REAR DERAILLEUR	Shimano Deore M7200, Shadow ES
BRAKES	Shimano BR-MT200, hydraulic, Shimano RT-10 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano BL-MT201
CASSETTE	Shimano Deore M6200, 10x51
CHAIN	KMC X-12
CRANKSET	ProWheel MPX, 32t (27.5) or 30t (29) XS: 165mm (27.5) S: 165mm (27.5) / 170mm (29) M: 170mm (29) L: 170mm (29) XL: 175mm (29) XXL: 175mm (29)
BOTTOM BRACKET	Cartridge

WHEELS	
RIMS	Giant tubeless compatible 29 or 27.5, alloy, double wall, 21mm inner width
HUBS	[F] Shimano, sealed bearing, 15x110 thru axle, [R] 12x142 thru-axle
SPOKES	stainless, 14g
TIRES	Maxxis Rekon 27.5x2.4" or Maxxis Rekon Race 29x2.4", wire bead
LIMITS	
MAX TIRE CLEARANCE	2.4"
MAX CHAINRING SIZE	32T

FRAME GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")	XL (29")
Seat Tube Length (mm)	345	375	380	420	450	480
Seat Post Insertion Depth (mm)	300	340	245	200	250	300
Seat Tube Angle	74.0°	74.0°	74.5°	74.5°	74.5°	74.5°
Top Tube Length (mm)	542	562	581	604	629	653
Head Tube Length (mm)	90	90	95	105	125	140
Head Tube Angle	67.0°	67.0°	67.5°	67.5°	67.5°	67.5°
Fork Rake (mm)	44	44	44	44	44	44
Trail (mm)	105	105	109	109	109	109
Wheelbase (mm)	1084	1104	1140	1164	1191	1216
Chain Stay Length (mm)	440	440	455	455	455	455
Bottom Bracket Drop (mm)	45	45	55	55	55	55
Stack (mm)	548	548	597	606	625	638
Reach (mm)	385	405	415	435	455	475
Stand Over Height (mm)	684	684	715	708	708	710
Handlebar Width (mm)	760	760	760	760	760	760
Stem Length (mm)	40	50	40	50	60	60
Crank Length (mm)	165	165	170	170	170	175

All prices and specifications are subject to change without notice.