



ESPECIFICACIONES

MARCO	
TALLAS	S, M, L, XL
COLORES	Chameleon Saturn / Carbon
MARCO	Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
TENEDOR	Fox 34 Float SC Performance Elite Live Valve, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
AMORTIGUADOR	Fox Performance Elite Live Valve, 165/45, custom tuned for Giant
COMPONENTES	
MANUBRIO	Giant Contact SLR XC Flat, composite, 760x35mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
ESPIGA	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
TUBO DE SILLÍN	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 440mm XL: 150mm travel / 30.9 x 445mm
SILLÍN	Fizik Antares R5 with Kium rails
PEDALES	N/A
TRANSMISIÓN	
PALANCAS DE CAMBIOS	Shimano Deore XT SL-M8100, 1x12
DESCARRILADOR	N/A
TENSOR	Shimano Deore XT RD-M8100
FRENOS	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-64 rotors [F]180mm, [R]160mm
LEVAS DE FRENOS	Shimano Deore XT BL-M8100
CASSETTE	Shimano Deore XT M8100, 10x51
CADENA	KMC X-12
BIELAS	Shimano Deore XT, 32t S:170mm, M:175mm, L:175mm, XL:175mm
EJE CENTRO	Shimano, press fit
RUEDAS	
RINES	Giant XCR 1 29 Carbon WheelSystem
MANZANAS	Giant XCR 1 29 Carbon WheelSystem
RADIOS	Giant XCR 1 29 Carbon WheelSystem
LLANTAS	Maxxis Recon Race 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

CARACTERÍSTICAS

- Marco: Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
- Tenedor: Fox 34 Float SC Performance Elite Live Valve, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
- Palancas de cambios: Shimano Deore XT SL-M8100, 1x12
- Bielas: Shimano Deore XT, 32t S:170mm, M:175mm, L:175mm, XL:175mm
- Colores: Chameleon Saturn / Carbon

GEOMETRÍA

MARCO	S	M	L	XL
Seat Tube Length (mm)	390	420	465	495
Seat Tube Angle	75,5°	75,5°	75,5°	75,5°
Top Tube Length (mm)	572	604	626	653
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	67,5°	67,5°	67,5°	67,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Wheelbase (mm)	1127	1159	1183	1212
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	42	42	42	42
Stack (mm)	589	593	603	612
Reach (mm)	420	450	470	495
Stand Over Height (mm)	745	750	777	800
Ancho de Manubrio (mm)	760	760	760	760
Largo de espiga (mm)	60	70	70	70
Largo de bielas (mm)	170	175	175	175
Tamaño de rueda	29"	29"	29"	29"

Todas las especificaciones anteriores están sujetas a cambios sin previo aviso. Imagen de referencia.