



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Digital Blurple/Raw Carbon
CUADRO	Advanced-grade composite front and rear triangles, 160mm Maestro suspension, flip chip, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, integrated downtube storage
HORQUILLA	Fox 38 Factory, 170mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
AMORTIGUADOR	Fox Float X2 Factory, 205/62.5, custom tuned for Giant
COMPONENTES	
MANILLAR	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
PUÑOS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
POTENCIA	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
TIJA DE SILLÍN	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm
SILLÍN	Giant Romero SL
PEDALES	platform
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS Pod, discrete clamp, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM GX Eagle Transmission
FRENOS	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]220mm, [R]200mm
PALANCAS DE FRENOS	Shimano SLX BL-M7100
CASSETTE	SRAM GX Eagle Transmission, 10x52
CADENA	SRAM GX Eagle Transmission
JGO. PLATOS Y BIELAS	SRAM GX Eagle Transmission, DUB, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
BUJES	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 30t 3-pawl driver, 6-bolt
RADIOS	Stainless steel
CUBIERTAS	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra, DD, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

GEOMETRÍA

CUADRO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Longitud del tubo del sillín (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	262			287			312			337
Ángulo del tubo del sillín	78,3°	78,7°	79,0°	78,3°	78,7°	79,0°	77,3°	77,7°	78,0°	77,3°
Longitud del tubo superior (mm) (mm)	556	555	555	587	586	585	620	620	619	652
Longitud del tubo de dirección (mm) (mm)	100			105			115			120
Ángulo del tubo de dirección	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°	63,9°	64,2°	63,5°
Inclinación de la horquilla (mm)	44			44			44			44
Trail (mm) (mm)	140	138	135	140	138	135	140	138	135	140
Distancia entre ejes (mm) (mm)	1214	1213	1212	1246	1245	1244	1271	1270	1269	1304
Longitud de la vaina (mm) (mm)	445	443	442	445	443	442	445	443	442	445
Caída del eje de pedaliador (mm) (mm)	35	30	25	35	30	25	35	30	25	35
Stack (mm) (mm)	627	624	622	632	629	626	641	638	635	645
Reach (mm) (mm)	426	430	434	456	460	464	476	480	484	506
Altura del suelo al tubo (mm) (mm)	720	724	729	735	739	744	751	756	760	746
Ancho del manillar (mm) (mm)	800			800			800			800
Longitud de la potencia (mm) (mm)	40			40			40			40
Longitud de las bielas (mm) (mm)	165			170			170			170
Tamaño de ruedas	29"			29"			29"			29"

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.