



ESPECIFICACIONES

CUADRO	
TALLAS	27.5: XS,S,M,L, 29: S,M,L,XL,XXL
COLORES	Cordovan, Cold Iron
CUADRO	ALUXX-grade aluminum, disc
TIJERA	SXC32-2 RL, air spring, QR, alloy steerer XS: 80mm travel (27.5) S: 80mm travel (27.5) / 100mm travel (29)
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Connect Trail, 31.8mm XS: 730mm (27.5) S: 780mm (27.5) / 780mm (29) M: 780mm (27.5) / 780mm (29)
GRIPS	Giant Sole-O
POTENCIA	Giant Sport, 7-degree XS: 40mm (27.5) S: 50mm (27.5) / 50mm (29) M: 60mm (27.5) / 60mm (29)
POSTE DE ASIENTO	Giant Sport, 30.9 XS: 300mm (27.5) S: 300mm (27.5) / 375mm (29) M: 375mm (27.5) / 375mm
ASIENTO	Giant custom
PEDALES	MTB caged
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano CUES SL-6000, 1x10
DESVIADOR	N/A
CAMBIO TRASERO	Shimano CUES RD-U6000
FRENOS	Tektro HDC M275, hydraulic, Tektro rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Tektro HDC M275
CASSETTE	Shimano CUES, CS-LG300, 11x48
CADENA	Shimano CUES LG500
MULTIPLICACIÓN	ProWheel Charm, 30t (27.5) or 32t (29) XS: 165mm (27.5) S: 170mm (27.5) / 170mm (29) M: 170mm (27.5) / 175m
EJE DE CENTRO	cartridge

RUEDAS	
RUEDAS	Giant GX03V 29 or 27.5, alloy, double wall, 21mm inner width
MAZAS	alloy, sealed bearing
RAYOS	stainless, 14g
NEUMÁTICOS	Kenda Booster 27.5 or 29x2.4", wire bead
EXTRAS	2.4" max tire size

GEOMETRÍA

CUADRO	S (29")	M (29")	L (29")	XL (29")
Longitud de la Base del Poste de Asiento (mm)	390	440	490	535
Seat Post Insertion Depth (mm)	245	200	250	300
Ángulo de la Base del Poste de Asiento	74.0°	74.0°	74.0°	74.0°
Longitud del Tubo Superior (mm)	577	599	620	639
Longitud del Telescopio (mm)	95	105	125	140
Ángulo del Telescopio	68.5°	68.5°	68.5°	68.5°
Rake (mm)	51	51	51	51
Trail (mm)	94	94	94	94
Distancia entre Ejes (mm)	1126	1150	1172	1192
Longitud de Vaina Inferior (mm)	455	455	455	455
Caída del Eje de Centro (mm)	55	55	55	55
Stack (mm)	602	611	630	644
Reach (mm)	404	424	439	454
Altura del Tubo Superior al Suelo (mm)	732	766	805	839
Ancho del Manubrio (mm)	780	780	780	780
Longitud de la Potencia (mm)	50	60	70	80
Longitud de la Biela (mm)	170	175	175	175
Tamaño de las Ruedas	29"	29"	29"	29"

Todas las especificaciones están sujetas a cambios sin previo aviso.