



## ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
MANDO	RideControl Ergo 3, grip integrated
PANTALLA	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
BATERÍA	EnergyPak Smart 625Wh, y EnergyPak Plus 250Wh extender compatible (solo tallas M, L, XL)
CUADRO	
TALLAS	S, M, L, XL
COLORES	Amber Glow
CUADRO	ALUXX SL-grade Aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, UDHTM derrailleur hanger
HORQUILLA	RockShox Domain R 29er, 170mm travel, 15x110 Boost, Maxle Stealth, E-bike Approved
AMORTIGUADOR	Fox Float DPS Performance, EVOL Large Volume sleeve, 2-position lever, 205x62.5mm Trunnion mount, custom tuned
COMPONENTES	
MANILLAR	Giant Contact Trail, 35x800mm
GRIPS	Giant Tactal Pro-E, single lock-on
POTENCIA	Giant Contact SL 35
TIJA DE SILLÍN	Giant Contact Switch, dropper, S: 125mm travel / 30.9 x 395mm M: 150mm travel / 30.9 x 440mm L: 170mm travel / 30.9 x 450mm XL: 170mm travel / 30.9 x 450mm
SILLÍN	Giant Romero Trail
PEDALES	Flat pedal
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore
DESVIADOR	MRP 1X HD2 custom co-molded chain guide
CAMBIO TRASERO	Shimano Deore 12-speed
FRENOS	Shimano Deore BR-M4120, 4-piston, hydraulic disc, 203mm
PALANCAS DE FRENOS	Shimano Deore BL-M4100, I-spec EV
CASSETTE	Shimano Deore CS-M6100-12, 10-51T, 12-speed
CADENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
JGO. PLATOS Y BIELAS	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S/M:160, L/XL:165)
CAJA DE PEDALIER	-
RUEDAS	
LLANTAS	Giant AM 29"[F] 27.5"[R], Tubeless ready, 30mm inner width
BUJES	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RADIOS	Sapim E-Lite [r] Race [f]
CUBIERTAS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F]Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESORIOS	

## CARACTERÍSTICAS

- Cuadro: ALUXX SL-grade Aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, UDHTM derrailleur hanger
- Horquilla: RockShox Domain R 29er, 170mm travel, 15x110 Boost, Maxle Stealth, E-bike Approved
- Manetas de cambio: Shimano Deore
- Jgo. platos y bielas: Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S/M:160, L/XL:165)
- Colores: Amber Glow

## GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud del tubo del sillín (mm)	400	425	450	475				
Ángulo del tubo del sillín	76,7°   77,5°	76,7°   77,5°	76,7°   77,5°	76,7°   77,5°				
Longitud del tubo superior (mm) (mm)	569   568	595   594	622   621	649   648				
Longitud del tubo de dirección (mm) (mm)	100	100	110	120				
Ángulo del tubo de dirección	63,7°   64,5°	63,7°   64,5°	63,7°   64,5°	63,7°   64,5°				
Inclinación de la horquilla (mm)	44	44	44	44				
Trail (mm) (mm)	135,5   132,1	135   132	135   132	135,5   132,1				
Distancia entre ejes (mm) (mm)	1209   1210	1236   1237	1265   1266	1295   1296				
Longitud de la vaina (mm) (mm)	454   454	454   454	454   454	454   454				
Caída de la caja de pedalier (mm) (mm)	25   15	25   15	25   15	25   15				
Stack (mm) (mm)	636   632	635   632	645   641	654   650				
Reach (mm) (mm)	425   430	450   455	475   480	500   505				
Altura del suelo al tubo (mm) (mm)	785   789	772   776	771   775	768   772				
Ancho del manillar (mm) (mm)	800	800	800	800				
Longitud de la potencia (mm) (mm)	40	40	50	50				
Longitud de las bielas (mm) (mm)	160	160	165	165				
Tamaño de ruedas	F29" / R27.5"	F29" / R27.5"	F29" / R27.5"	F29" / R27.5"				

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.